



# NetVanta 3200

## Modular Access Router Supporting up to an E1 of Bandwidth

### Product Features

- Modular Network Interface Module (NIM) offering flexibility
- Modular Dial Backup Interface Module (DIM) guaranteeing bandwidth
- Stateful inspection firewall for network security
- Quality of Service (QoS) for delay-sensitive traffic like Voice over IP (VoIP)
- Optional DSX-1 interface supplies TDM voice transport
- Comprehensive PPP dial backup scheme prevents network downtime
- VLAN Trunking (802.1Q) for routing between VLANs
- Network Address Translation (NAT) for IP Address Concealing
- Optional Virtual Private Network (VPN) for secure corporate connectivity across the Internet
- Recognizable Command Line Interface (CLI) and intuitive Web-based Graphical User Interface (GUI)
- Built-in DSU/CSU for circuit protection
- Feature-rich ADTRAN Operating System (AOS)
- Industry-leading support, service, and warranty

The NetVanta 3000 Series of modular access routers is designed for cost-effective Internet access, corporate Frame Relay, point-to-point connectivity, ADSL, and VPN. The NetVanta 3000 Series currently consists of the NetVanta 3200, 3205, and 3305 with a variety of interchangeable NIMs and DIMs.

#### Modular Hardware

The NetVanta 3200 is a single-slot, single-Ethernet standalone unit in a plastic housing. A single slot within any of the NetVanta 3000 Series will house a variety of NIMs and DIMs, which include an E1/FE1, E1/FE1 with G.703, ADSL, SHDSL, Serial, T1/FT1, T1/FT1 with DSX-1, Dual T1s, or a 56/64k interface. For dial backup, an ISDN BRI U-Interface DIM or an S/T-Interface DIM is available for preventing downtime by dialing around a failed circuit to any PPP-compliant device.

#### Standards Protocols

The versatile hardware platform of the NetVanta 3200 is further complemented with the AOS. The AOS allows for the support of static and default routes, demand routing, and allows for fast, accurate network convergence using routing protocols such as BGP, OSPF, and RIP. In addition, the AOS terminates Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, and HDLC WAN protocols. Multihoming is also available to provide redundant or backup Wide Area Network (WAN) links to multiple ISPs, guaranteeing a wide-area connection.

#### Security

For added security, the AOS provides a powerful, high performance stateful inspection firewall. It will examine all incoming and outgoing packets against the security policies established by the IT manager. In addition, the firewall can identify and protect against common Denial of Service (DoS) attacks like TCP syn flooding, IP spoofing, ICMP redirect, ping-of-death, and IP reassembly problems. With the AOS Enhanced Feature Pack Upgrade, the NetVanta 3000 Series adds the support for IPSec-compliant VPN. The NetVanta 3200 supports up to five simultaneous VPN tunnels,

while supporting encryption algorithms like DES, 3DES, and AES. With this upgrade, the NetVanta 3200 is fully compatible with other IPSec VPN-equipped NetVanta products.

#### QoS

QoS is also supported for delay-sensitive traffic like VoIP or video. To prioritize mission-critical traffic and control network congestion, the NetVanta 3200 uses Low Latency Queuing, Weighted Fair Queuing (WFQ), Class-based WFQ, and DiffServ marking to establish priority of IP packets routed over the WAN.

#### VoIP Ready

In combination with the QoS features, a specialized Session Initiation Protocol (SIP) Application Layer Gateway (ALG) allows SIP traffic to traverse Network Access Translation (NAT)-enabled firewalls. For an enterprise network, this interoperability allows IP PBXs, phones, and other SIP-based devices to set up, tear down, and pass voice and call control messages seamlessly through the integral NAT-enabled firewall.

#### Administration

AOS offers a standard CLI that mimics the widely adopted, industry *de facto* standard. The sequence of commands required to configure similar devices is almost identical, eliminating training costs typically associated with learning a new operating system or obtaining costly industry certifications. The CLI also allows for configuration scripts to be used, saved, and downloaded for a quick-and-easy recovery mechanism. In addition, an intuitive GUI provides step-by-step configuration wizards, management capability, and the ability to upload firmware updates.

ADTRAN, the leader in WAN connectivity, offers reliable equipment that increases network performance, lowers cost, and positions networks for the future. In addition, these products are backed by an industry-leading warranty, free firmware downloads, and world-class technical support from ADTRAN.



### ADTRAN, Inc.

International Department  
901 Explorer Boulevard  
Huntsville, Alabama 35806  
USA

[www.adtran.com/global](http://www.adtran.com/global)

#### U.S. Headquarters

+1 256 963 8000

+1 256 963 6300 fax

[international@adtran.com](mailto:international@adtran.com)

#### International Customer Service

+1 256 963 8716 voice

#### Asia—Beijing, China

+86 10 8527 5011

+86 10 8527 5010 fax

[sales.china@adtran.com](mailto:sales.china@adtran.com)

#### Hong Kong

+852 3187 7111

+852 2116 4084 fax

[sales.asia@adtran.com](mailto:sales.asia@adtran.com)

#### Asia—Bangkok, Thailand

+66 2 625 3085

+66 2 625 3142 fax

[sales.asia@adtran.com](mailto:sales.asia@adtran.com)

#### Asia—Singapore

+65 6248 4665

+65 6320 8521 fax

[sales.asia@adtran.com](mailto:sales.asia@adtran.com)

#### Australia/New Zealand—

##### Melbourne, Australia

+61 3 9658 0500

+61 3 9658 0599 fax

[sales.australia@adtran.com](mailto:sales.australia@adtran.com)

#### Australia/New Zealand—

##### Sydney, Australia

+61 2 9959 2485

+61 2 9959 2244 fax

[sales.australia@adtran.com](mailto:sales.australia@adtran.com)

#### Canada—Montreal, Quebec

+1 877 923 8726

+1 514 940 2888

+1 514 989 3198 fax

[sales.canada@adtran.com](mailto:sales.canada@adtran.com)

#### Canada Headquarters—Toronto,

##### Ontario

+1 877 923 8726

+1 514 989 3198 fax

[sales.canada@adtran.com](mailto:sales.canada@adtran.com)

#### EMEA Regional Headquarters—

##### United Kingdom

+44 1256 884055

+44 1256 884056 fax

[sales.emea@adtran.com](mailto:sales.emea@adtran.com)

[sales.europe@adtran.com](mailto:sales.europe@adtran.com)

#### Mexico/Central America/

##### Caribbean—USA

+1 256 963 4833

+1 256 963 6300 fax

[sales.latin@adtran.com](mailto:sales.latin@adtran.com)

[sales.caribbean@adtran.com](mailto:sales.caribbean@adtran.com)

[sales.mexico@adtran.com](mailto:sales.mexico@adtran.com)

[sales.ai@adtran.com](mailto:sales.ai@adtran.com)

#### South America—USA

+1 256 963 3113

+1 256 963 6300 fax

[sales.latin@adtran.com](mailto:sales.latin@adtran.com)

[sales.brazil@adtran.com](mailto:sales.brazil@adtran.com)

[sales.ai@adtran.com](mailto:sales.ai@adtran.com)



ADTRAN is an ISO 9001, ISO 14001,  
and a TL 9000 certified supplier.

i61202860L1-8K AOS 17.1 November 2007  
Copyright © 2007 ADTRAN, Inc.  
All rights reserved.

# NetVanta 3200



## Modular Access Router Supporting up to Two T1s of Bandwidth

### Physical Interface

- **NIM:** E1/FE1, E1/FE1 with G.703, ADSL, SHDSL, Serial, T1/FT1, T1/FT1 with DSX-1, Dual T1, and 56/64k
- **DIM:** ISDN BRI (U and S/T)
- **LAN:** Auto-sensing 10/100Base-T Full Duplex (RJ-45)
- Console Port

### Diagnostics LEDs

- Power
- **WAN:** link, transmit, receive
- **LAN:** link, transmit, receive
- **Dial backup:** transmit and receive

### Processor and Memory

- 80 MHz, Motorola MPC 866
- **RAM:** 32 MB
- **FLASH:** 16 MB

### Security

#### Firewall

- Stateful Inspection Firewall
- Denial of Service (DoS) Protection
- Access Control Lists
- Application Level Gateways (ALGs)

#### Network Address Translation

- Basic NAT (1:1), NAPT (Many:1), and 1:1 Port Translation
- NAT compatible SIP ALG

#### Secure Management

- Multi-level access control
- RADIUS AAA
- TACACS+
- SSH CLI and SSL GUI
- Port Authentication (802.1x)

#### Optional Virtual Private Network (VPN)

- **IPSec Tunnel Mode:** 5 Tunnels
- **Encryption:** DES, 3DES, and AES
- **Diffie Hellman Group Support:**
  - Group 1: MODP 768
  - Group 2: MODP 1024
- **Hash Algorithms:** MD5-HMAC and SHA1-HMAC
- **Authentication Mechanisms:**
  - XAUTH
  - Secure ID
  - X.509 Digital certificates
  - DSS Signatures
  - Preshared keys

- **Key Management:** IKE (ISAKMP/Oakley)

#### ■ IKE Modes:

- Main
- Perfect Forward Secrecy
- Aggressive
- Mode Config

- Dead Peer Detection

- NAT Traversal V2

### Quality of Service (QoS)

- Class-based Weighted Fair Queuing, Low Latency, and Weighted Fair Queuing
- DiffServ Packet Marking and Recognition
- Frame Relay Fragmentation

### Protocols

- eBGP/iBGP
- OSPF
- RIP (v1 and v2)
- Demand Routing
- GRE
- IGMP v2
- ATM (ADSL)
- Frame Relay
- Multilink Frame Relay
- PPP
- PPPoE
- PPPoA
- RFC 1483
- Multilink PPP
- HDLC
- PPP Dial Backup
- PAP and CHAP
- Multihoming

### Frame Relay

- Point-to-point
- RFC 1490 Encapsulation
- LMI types: LMI, ANSI (Annex D), CCITT (Annex A) and Static

### DHCP

- Client, Server, and Relay

### Administration

- Familiar Command Line Interface (CLI)
- Web-based GUI
- n-Command support
- SNMP v3
- SYSLOG logging
- Email alerts (SMTP)
- Policy statistics

### Environment

- **Operating Temperature:** 0° to 50 °C (32° to 122 °F)
- **Storage Temperature:** -20° to 70 °C (-4° to 158 °F)
- **Relative Humidity:** Up to 95%, non-condensing

### Physical

- **Chassis:** Self-standing—4.1cm W, 22.8cm H, 16.2cm D
- **Weight:** 1Kg
- **Power:** 12 VDC, 800 mA, 6 W max.  
(120 VAC AC to DC power adapter included)

### Agency Approvals

- FCC Part 68
- Industry Canada CS03
- UL and Canadian UL (CUL), IEC/EN, CSA
- Australian C-tick (Chassis), A-tick (NIMs)
- CE Mark
- RoHS

## Ordering Information

Equipment	Part #
<b>NetVanta 3200 Chassis</b>	
with US Power	1202860E1
with International Power	4200860E1#IN
<b>NetVanta 3200 Chassis with VPN</b>	
with US Power	4200860E2
with International Power	4200860E2#IN
<b>Enhanced Feature Pack</b>	
VPN Software Upgrade	1950860E2

ADTRAN believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. ADTRAN and NetVanta are registered trademarks of ADTRAN, Inc. and its affiliates in the U.S. and certain other countries. All other trademarks mentioned in this document are the property of their respective owners. Five-year warranty applies only to products sold in North America.

ADTRAN products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding ADTRAN's export license, please visit [www.adtran.com/exportlicense](http://www.adtran.com/exportlicense)