

# Release Bulletin

## OmniCONNECT™ Release 10.5 for Digital OpenVMS VAX

### 1. Product Summary

---

Enclosed is OmniCONNECT release 10.5, which is compatible with the following platform and operating system configurations:

- DEC VAX OpenVMS versions 5.4-1a – 6.0

#### 1.1. Operating System Patch

---

The following operating system patch is **required** for all systems that perform a lot of paging and is **recommended** for other systems as well:

Patch Number: CSCPAT\_1084\_018

Engineering Cross Reference:

AXPSMUP01\_010, VAXSMUP01\_U2055, AXPSYS02\_010,  
AVMASYS013015, AXPSYS03\_015

This patch is for the page management bug fix. It can be applied on OpenVMS VAX versions 5.0–5.5.2. It **cannot** be applied on OpenVMS VAX version 5.43, 5.5-1, or 5.5-2 if you have installed patch number CSCPAT\_2026 or CSCPAT\_2027.

### 2. Special Installation Instructions

---

The following installation instructions should be noted. They are not described in the *OmniCONNECT Installation Guide*.

Copyright © 1989–1995 by Sybase, Inc. All rights reserved. SYBASE, the SYBASE logo, Data Workbench, DBA Companion, Deft, Gain *Momentum*, PowerBuilder, Powersoft, SQL Advantage, SQL Debug, Transact-SQL, ADA Workbench, Applications from Models, APT-Build, APT-Edit, APT-Execute, APT-Translator, APT Workbench, AnswerBase, Backup Server, Build *Momentum*, Client-Library, Configurator, DB-1Library, Embedded SQL, Enterprise Builder, Enterprise Client/Server, Enterprise Meta Server, Enterprise Modeler, Enterprise *Momentum*, Gain, InfoMaker, MAP, MDI, Navigation Server, Net-Gateway, Net-Library, Object *Momentum*, OmniSQL Access Module, OmniSQL Gateway, OmniSQL Server, Open Client, Open Client/Server Interfaces, Open Gateway, Open Server, PC DB-Net, PostDoc, Replication Agent, Replication Driver, Replication Server, Replication Server Manager, Report Workbench, RW-Library, Secure SQL Server, SQL Server Manager, SQL Server Monitor, SQL Server, SQL Toolset, SQR Workbench, Sybase *Momentum*, SyBooks, System 10, The Enterprise Client/Server Company, Watcom SQL, WorkGroup SQL Server, XA-Library, and XA-Server are trademarks of Sybase, Inc. Other product names used herein may be trademarks or registered trademarks of Sybase or other companies.

## 2.1. Primary and Secondary Installations

---

It is important to define the SYBASE\_SYSTEM logical properly in order to avoid overwriting existing installations as discussed in Chapter 2 of the *OmniCONNECT Installation Guide*.

The following examples define the SYBASE\_SYSTEM logical for primary and secondary installations.

### 2.1.1. Use System Logicals for Primary Installations

---

In this example the target location for the rooted system logical is device *DUA0* in the named directories.

```
DEFINE /SYSTEM /EXECUTIVE /TRANSLATION=(CONCEALED, TERMINAL) -
OMNIMAIN DUA0:[PRODUCTION.REL105.]
DEFINE /SYSTEM /EXECUTIVE SYBASE_SYSTEM OMNIMAIN
```

### 2.1.2. Use Process Logicals for Secondary Installations

---

The target location for a rooted process logical is a different location than the primary installation.

```
DEFINE /TRANSLATION=(CONCEALED, TERMINAL) -
OMNITEST DUA2:[BETATEST.REL1051.]
DEFINE SYBASE_SYSTEM OMNITEST
```

## 2.2. Upgrading and *sp\_configure*

---

If you are migrating data from OmniSQL Server release 10.1.2 to OmniCONNECT release 10.5, note that configuration variables existing in the old OmniSQL Server release 10.1.2 will not automatically be propagated to the new OmniCONNECT release 10.5. If you want to change configuration variables in the new server, run *sp\_configure*.

## 3. Technical Support

---

If you have any questions about this installation or need assistance during the installation process, please contact Sybase Technical Support or the Sybase subsidiary in your area.

Please contact the distributor from which your software was purchased if you do not know how to contact Sybase Technical Support.

## 4. Documentation Updates and Clarifications

---

The following updates and clarifications should be noted.

### 4.1. *defgen*

---

*defgen* maps *smallmoney* and *money* datatypes to *float*, and the *smalldatetime* datatype to *datetime* for SYBASE SQL Server™ release 4.9 and Microsoft SQL Server 4.21 tables.

The datatype mapping can be used as is, or the SQL script produced by *defgen* can be modified to use the native SQL Server datatypes.

### 4.2. Oracle and Ingres Access

---

OmniCONNECT is designed to access Oracle and Ingres databases through DirectCONNECT™ servers that are defined with server class *access\_server*. These DirectCONNECT products are not available yet.

Sites requiring immediate access to Oracle and Ingres databases can use OmniSQL Server™ release 10.1.2. Configure OmniCONNECT 10.5 to access the 10.1.2 server as server class *sql\_server*.

This configuration should be limited to read-only access.

Transactional integrity is not guaranteed and users may encounter deadlocks during updates and deletes.

The *migrate* utility will not be able to migrate OmniSQL Server 10.1.2 Oracle and Ingres objects into OmniCONNECT 10.5 until the DirectCONNECT servers are available and installed.

### 4.3. Informix Access

---

OmniCONNECT 10.5 is fully compatible with the OmniSQL Server Informix Access Module 10.1.2. This access module should be defined to your OmniCONNECT with server class *generic*.

This OmniCONNECT configuration has specific Informix Access Module EBF-level requirements, depending on the platform where

the OmniSQL Server Informix Access Module release 10.1.2 is running.

- HP – EBF 5377
- Sun4 – EBF 5378
- AIX – EBF 5379

#### 4.4. Rdb Access

---

OmniCONNECT 10.5 is fully compatible with the OmniSQL Server Rdb Access Module 10.1.2. This access module should be defined to your OmniCONNECT with server class *generic*.

This OmniCONNECT configuration has specific Rdb Access Module EBF-level requirements, depending on the platform where the OmniSQL Server Rdb Access Module release 10.1.2 is running.

- AXP/VMS – EBF 4498
- VAX/VMS – EBF 4499

#### 4.5. *update statistics without checkpoint*

---

If you perform **update statistics** to enable the optimizer to choose the proper join order but do not immediately execute **checkpoint** or perform an orderly shutdown afterwards, then you could lose the update statistics information. Conditions such as **kill** (or **STOP/ID**), or **Ctrl-C** (or **Ctrl-Y**) which terminate the server in a non-orderly fashion, cause the update statistics information to be lost.

If a **checkpoint** is issued within the database where the **update statistics** is invoked, then all statistics information will be preserved.

#### 4.6. OmniCONNECT Rejects Connect Request

---

A connection to OmniCONNECT may be rejected with no error or warning message under the circumstances described.

When OmniCONNECT is started, there is a platform-specific maximum number of connections that can be established. This is determined by the operating system. OmniCONNECT provides the **sp\_configure** option **maximum ctlib connections**. There is a default value, and the number can be explicitly configured to a higher or lower value. If the operating system value is less than the **sp\_configure** value,

OmniCONNECT rejects all connection requests exceeding the operating system configuration.

#### 4.7. Optimization for Remote Views

---

OmniCONNECT release 10.5 requires indexes on tables in order to optimize queries. Since views cannot have indexes, when an OmniCONNECT release 10.5 table is mapped to a remote view no indexes will be found. Hence, OmniCONNECT will not be able to properly optimize access to the table.

To help OmniCONNECT optimize access to remote views the **9808** trace flag should be used. This trace flag instructs OmniCONNECT to do the following on the receipt of a `create index` command:

- create the index in OmniCONNECT catalogs
- Do **not** create indexes on remote data source
- After creating all indexes on the table, perform the `update statistics` command on the table. This will cause OmniCONNECT to build and save distribution statistics on the table. These statistics will be used during query optimization in order to pick the most efficient index on a table and to choose the proper join order.

The result is that a local index is created in OmniCONNECT, but an index is not created on the remote data source. OmniCONNECT can then use the index for query optimization.

Note that the **9808** trace flag should be turned off after the required indexes are created.

The following is an example:

```
1> dbcc traceon (9808)
2> go
1> create unique clustered index au_id_ind
on authors(au_id)
2> go
1> dbcc traceoff (9808)
2> go
1> update statistics authors
2> go
```

## 5. Highlighted Known Problems

---

### 5.1. *create table* and Primary Key

---

OmniCONNECT release 10.5 will generally ignore the primary key attribute in a `create table` statement. However, when creating tables using the RMS access method, the primary key attribute is not completely ignored. As a result OmniCONNECT thinks there is an index, although no index was created. In addition, it is not possible to create the index because OmniCONNECT thinks it already exists. The workaround is to remove the primary key attribute prior to creating the tables.

### 5.2. Limitations on Packet Size

---

The `/tdspacketsize` option specifies the network packet size to be used for an `isql` or `bcp` session. The maximum packet size currently supported is 32,256 bytes. Specification of a packet size of 32,768 bytes or greater will result in errors similar to the following:

In the OmniCONNECT error log:

```
kernel nast_readpost: Invalid tdslength (-32768), socket 1,  
listener 0
```

In the client error log:

```
SYSTEM-F-LINKDOXCON, network partner disconnected logical link  
DB-LIBRARY error: Write to OmniCONNECT failed.  
SYBASE-E-BCPFAIL, BCP has failed.
```

### 5.3. *bcp* Batch Size

---

When running the `bcp` utility against OmniSQL Server, errors occur if the `bcp` batch size is non-zero.

### 5.4. Implicit Conversions Involving *datetime*

---

A query containing a join between dissimilar *datetime* columns may generate unpredictable results. For example:

```
select * from t1 where smalldatetimocol = datetimocol
```

will not always result in the correct number of rows returned.

### 5.5. *sp\_statistics* and Access Module for DB2

---

OmniCONNECT sites that include the OmniSQL Access Module for DB2 (SYRT) in a configuration may experience a problem with the *sp\_statistics* catalog stored procedure issued by the DB2 Access Module.

One symptom can be incorrect column names for a table when a *create existing table* command is issued. This happens when the underlying table and index names are the same as another table and index set, but have a different creator.

The user can issue an *sp\_help* command against the table and check for accurate indexes.

