

Storage Engine, Data Inconsistency between Replicas Found in PLDB, Minor Ericsson Centralized User Database

OPERATING INSTRUCTION

Copyright

© Ericsson AB 2015, 2016. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Introduction	1
1.1	Alarm Description	1
1.2	Prerequisites	2
2	Procedure	5
	Glossary	7
	Reference List	9



Storage Engine, Data Inconsistency between Replicas Found in PLDB, Minor



1 Introduction

This instruction concerns alarm handling for the Storage Engine, Data Inconsistency between Replicas Found in PLDB, Minor alarm.

1.1 Alarm Description

This alarm is raised as a result of issues found when running a Consistency Check on a Processing Layer Database (PLDB) slave replica by means of the `cudbConsistencyMgr` command. For further information about the command, refer to *CUDB Node Commands and Parameters*, Reference [1]. For more information about Consistency Check, refer to *CUDB Consistency Check*, Reference [2].

The alarm is issued in the following situation:

- The number of divergences between the slave replica and its master replica is lower than the threshold (default or selected value).

The possible alarm causes and the corresponding fault reasons, fault locations, and impacts are described in Table 1.

Table 1 Alarm Causes

Alarm Cause	Description	Fault Reason	Fault Location	Impact
Divergences between the slave replica and its master replica.	The number of divergences between the slave replica and its master replica found when running a consistency check is lower than the threshold.	Wrong backup restored on the slave replica.	Affected PLDB replica.	If this slave replica becomes the master replica, there might be a service impact for the subscribers affected by the data inconsistency.
		Slave replica addressed by faulty maintenance operation.		

Table 2 Alarm Attributes

Attribute Name	Attribute Value
Auto Cease	No
Module	STORAGE-ENGINE
Error Code	21
Timestamp First	Date and time when the alarm was raised for the first time.
Repeated Counter	Number which indicates how many times the alarm was raised.
Timestamp Last	Date and time of the most recent alarm raised.
Resource ID	.1.3.6.1.4.1.193.169.1.1.21.<NODE1>.<NODE2>
Alarm Model Description	Data inconsistency between replicas found, Storage Engine.



Attribute Name	Attribute Value
Alarm Active Description	Storage Engine (PLDB): Data inconsistency between replicas found, minor, nodes #<NODE1> and #<NODE2> (task <TASKID>).
ITU Alarm Event Type	processingErrorAlarm (4)
ITU Alarm Probable Cause	databaseInconsistency (160)
ITU Alarm Perceived Severity	(5) - Minor
Originating Source IP	Node ID where the alarm was raised.
Sequence Number	Number which indicates the order in which alarms were raised.

In Table 2, the indicated variables are as follows:

- <NODE1> is the CUDB Node Identifier the first PLDB replica is located at.
- <NODE2> is the CUDB Node Identifier the second PLDB replica is located at.
- <TASKID> is the identifier of the check task.

1.2 Prerequisites

This section provides information on the documents, tools, and conditions that apply to the procedure.

1.2.1 Documents

Before starting this procedure, ensure that you have read the following documents:

- *CUDB Node Fault Management Configuration Guide*, Reference [3], regarding alarm configuration.
- The section on the `cudbConsistencyMgr` command in *CUDB Node Commands and Parameters*, Reference [1].
- *CUDB LDAP Interwork Description*, Reference [4] and *CUDB Consistency Check*, Reference [2] regarding the LDAP tree log file and Consistency Check.
- *CUDB System Administrator Guide*, Reference [6] regarding the location of master replicas.
- *CUDB Backup and Restore Procedures*, Reference [5] regarding the combined unit data backup and restore procedure.
- *System Safety Information*, Reference [8].
- *Personal Health and Safety Information*, Reference [9].

**1.2.2****Tools**

Not applicable.

1.2.3**Conditions**

Not applicable.





2 Procedure

When this alarm is raised, perform the following steps:

1. Locate and identify the Lightweight Directory Access Protocol (LDAP) tree log based on the `<NODE1>`, `<NODE2>`, and `<TASKID>` parameters in the alarm as follows:
 - a. Find the CUDB node with ID `<NODE1>`.
 - b. Search for the `/local/cudb_ddci/replica_check/cudbDs uDiff_op_TASKID*.xml` file on both System Controllers (SCs) of the node.
2. Align the slave replica to its master in the PLDB as follows:
 - If this node is still a PLDB slave node, and the node with ID `<NODE1>` is still the master node of the PLDB, perform a combined unit data backup and restore on the PLDB against this CUDB node.

Note: When performing a PLDB restore, the `cudbUnitDataBackupAndRestore` command does not work, just exits with an error message, if any of the DS clusters in the node is the master replica of its data partition. Therefore, it is required to move the DSG masterships manually before performing the PLDB restore.

Also, if the PLDB has more than one slave, then consider ordering consistency check for the rest of slaves after restoring the backup.

- If this node (which was the checked slave at the time of the check) has become a PLDB master node since raising the alarm, perform a combined unit data backup and restore on the PLDB against the CUDB node with ID `<NODE1>`.

Note: Do not perform combined backup and restore if that has been done since the mastership change of the PLDB.

Also, when performing a PLDB restore, the `cudbUnitDataBackupAndRestore` command does not work, just exits with an error message, if any of the DS clusters in the node is the master replica of its data partition. Therefore, it is required to move the DSG masterships manually before performing the PLDB restore.

Finally, if the PLDB has more than one slave, then consider ordering consistency check for the rest of slaves after restoring the backup.



- In any other cases, ignore the results. Consider that the PLDB may not be consistent and further checks—involving the new master—are needed to verify it.
3. Analyze the LDAP tree log file as described below to find the data impacted by the inconsistency:
 - For impacted entries in the `ou=identities,<rootDn>` branch, validate the subscribers with those public identities, or consider reprovisioning them. Refer to the application Front End (FE) documentation for the procedure to validate or reprovision subscribers.
 - For impacted entries in the `ou=mscCommonData,<rootDn>` or `ou=servCommonData,<rootDn>` branches, validate or reprovision the impacted entry. Refer to the application FE documentation for the procedure to validate or reprovision common data.
 - For impacted entries in the `ou=admin,<rootDn>` branch, validate that the LDAP user data is correct, or delete, then add again the impacted LDAP user by following the procedure described in *CUDB System Administrator Guide*, Reference [6].

Refer to *CUDB LDAP Interwork Description*, Reference [4] for more information on the CUDB Main Directory Information Tree (DIT).

4. If the LDAP tree log contains an internal error, notify the next level of support. To interpret the contents of the LDAP tree log, refer to *CUDB Consistency Check*, Reference [2].
5. Clear the alarm manually as described in *CUDB Node Fault Management Configuration Guide*, Reference [3].

To find out where the master replicas are, refer to *CUDB System Administrator Guide*, Reference [6]. For further information about the combined unit data backup and restore procedure, refer to *CUDB Backup and Restore Procedures*, Reference [5].



Glossary

For the terms, definitions, acronyms, and abbreviations used in this document, refer to *CUDB Glossary of Terms and Acronyms*, Reference [7].



Storage Engine, Data Inconsistency between Replicas Found in PLDB, Minor



Reference List

CUDB Documents

- [1] *CUDB Node Commands and Parameters*
- [2] *CUDB Consistency Check*
- [3] *CUDB Node Fault Management Configuration Guide*
- [4] *CUDB LDAP Interwork Description*
- [5] *CUDB Backup and Restore Procedures*
- [6] *CUDB System Administrator Guide*
- [7] *CUDB Glossary of Terms and Acronyms*

Other Ericsson Documents

- [8] *System Safety Information*
- [9] *Personal Health and Safety Information*