

Delete Scheduled Event

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	1
2.1	Delete Scheduled Event	1



Delete Scheduled Event



1 Description

This instruction describes how to delete a scheduled event. Deleting a scheduled event prevents the associated scheduled backups from occurring.

A scheduled event can be deleted when no longer needed due to, for example, a new preventive maintenance strategy.

2 Procedure

2.1 Delete Scheduled Event

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - The backup type is known.
 - The scheduled event type is known, that is, `BrmSingleEvent`, `BrmPeriodicEvent`, or `BrmCalendarBasedPeriodicEvent`.
 - The scheduled event name is known.
 - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

Steps

1. Navigate to the `BrmBackupScheduler` managed object, for example:

```
>dn ManagedElement=N0DE06ST,SystemFunctions=1,BrM=1,BrmBackupMa  
nager=SYSTEM_DATA,BrmBackupScheduler=SYSTEM_DATA
```

2. Enter Config mode:

```
(BrmBackupScheduler=SYSTEM_DATA)>configure
```

3. Delete the scheduled event, for example:

```
(config-BrmBackupScheduler=SYSTEM_DATA)>no BrmSingleEvent=S_E  
VENT_20140428_152
```



Note: If the scheduled event name is unknown, use command **show**. The event names are listed at the end of **progressReport** of **BrmBackupScheduler**.

4. Commit the change:

```
(config-BrmBackupScheduler=SYSTEM_DATA)>commit
```

5. Verify that the event has been deleted:

```
(BrmBackupScheduler=SYSTEM_DATA)>show -v
```

The following is an example output:

```
BrmBackupScheduler=SYSTEM_DATA
[...]
  progressReport
[...]
    progressPercentage=100
    result=SUCCESS
[...]
    state=FINISHED
[...]
  BrmPeriodicEvent=P_EVENT_20140428_204
```

The event is no longer shown at the end of the **BrmBackupScheduler** progress report.