

Delete Custom Rule

OPERATING INSTRUCTIONS

Copyright

© Ericsson AB 2016, 2017. All rights reserved. No part of this document may be reproduced in any form without the written permission of the copyright owner.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Trademark List

All trademarks mentioned herein are the property of their respective owners. These are shown in the document Trademark Information.



Contents

1	Description	1
2	Procedure	1
2.1	Delete Custom Rule	1



Delete Custom Rule



1 Description

This instruction describes how to delete a custom rule.

The administrator can delete custom rules when they are no longer needed by the organization authorization policy.

2 Procedure

2.1 Delete Custom Rule

Prerequisites

- No documents are required.
- No tools are required.
- The following conditions must apply:
 - The user has the System Security Administrator role.
 - The CustomRule MO to delete is known.
 - An Ericsson Command-Line Interface (ECLI) session in Exec mode is in progress.

Steps

1. Navigate to the LocalAuthorizationMethod MO, for example:

```
>dn ManagedElement=N0DE06ST,SystemFunctions=1,SecM=1,UserManagement=1,LocalAuthorizationMethod=1
```

2. View the current settings:

```
(LocalAuthorizationMethod=1)>show -v
```

The following is an example output:



```
LocalAuthorizationMethod=1
[...]  
  CustomRule=Custom_FaultManagement_1  
  CustomRule=Custom_PerformanceManagement_1  
  CustomRule=Custom_SoftwareInventory_1  
  CustomRule=Custom_SoftwareManagement_1  
  CustomRule=Custom_SystemManagement_1  
  CustomRule=Custom_Top_1  
  CustomRule=Custom_Top_2  
  CustomRule=Custom_Top_3  
[...]
```

3. Enter Config mode:

```
(LocalAuthorizationMethod=1)>configure
```

4. Delete the CustomRule MO, for example:

```
(config-LocalAuthorizationMethod=1)>no CustomRule=Custom_SoftwareInventory_1
```

5. Commit the deletion:

```
(config-LocalAuthorizationMethod=1)>commit
```

6. Verify the deletion by checking the CustomRule instances:

```
(LocalAuthorizationMethod=1)>show -v
```

The following is an example output:

```
LocalAuthorizationMethod=1
[...]  
  CustomRule=Custom_FaultManagement_1  
  CustomRule=Custom_PerformanceManagement_1  
  CustomRule=Custom_SoftwareManagement_1  
  CustomRule=Custom_SystemManagement_1  
  CustomRule=Custom_Top_1  
  CustomRule=Custom_Top_2  
  CustomRule=Custom_Top_3  
[...]
```

7. The custom rule has been deleted from the managed element.