

TP194993 TAPE GUIDE

APPARATUS AFFECTED: 28A, 28B, 28C, 28D, 28E, 28F, 28G, 28J, 28J-1, 28K, 28L, 28M Typing Reperforator Units; 28A, 28D, 28D-1, 28D-2, 28D-3, 28D-4, 28D-6, 28E, 28F, 28F-1, 28F-2 Reperforator-Transmitter Units; 28D, 28E, 28G-1, 28K Perforator-Transmitter-Bases.

OBJECT: To facilitate adjustment of units equipped with the TP194993 tape guide.

CHANGE: Requirements given in Section 573-117-700, issue 3, paragraph 2.50, for the *PERFORATOR POSITION* (1); Section 573-118-700, issue 6, paragraph 2.05, for the *PUNCH MOUNTING POSITION* (2); Teletype Bulletins 247B, change 5, page 1-17, for the *PERFORATOR POSITION* (2); 250B, change 3, page 1-38, for the *PERFORATOR POSITION* (1) are changed to:

Punch Mechanisms for Chadless Tape

To check:

With the unit in the stop position and the typewheel in the letters field.

Requirement:

Clearance between the top of the rear leg of the stripper platform on the punch block and the typewheel character "Z".

MIN. 0.090 inch — MAX. 0.110 inch

Punch Mechanisms for Fully Perforated Tape

To Check:

With the unit in the stop position and the typewheel in the figures field.

Requirement:

Clearance between the top of the rear leg of the stripper platform on the punch block and the typewheel character "5".

MIN. 0.075 inch — MAX. 0.095 inch

IDENTIFICATION: Not involved.

INTERCHANGEABILITY: Not involved.

CLASSIFICATION FOR APPARATUS FURNISHED BY TELETYPE: This change is now in effect.

W.E.CO. STOCK OF OLD STYLE PARTS: Not involved.

APPLICATION TO APPARATUS IN THE FIELD: The new adjustment may be applied.

APPLICATION AT W.E.CO. DIST. HOUSE REPAIR SHOPS: The new adjustment may be used.