

**OUTPULSER AND TEST FRAME
AUTOMATIC NUMBER IDENTIFICATION-TYPE C
NO. 1, 350A, 355A, AND 35E97 OFFICES
EQUIPMENT DESIGN REQUIREMENTS
STEP-BY-STEP SYSTEMS**

1. GENERAL

1.001 This addendum supplements Practice 814-204-151, Issue 5.

1.002 The addendum is issued to provide information for:

- (a) A KP pulse delay.
- (b) Additional contact protection when the outpulser is associated with three or more number network and identifier frames.
- (c) Additional contact protection networks for noise suppression.

◆ (d) A change in contact protection when the outpulser is associated with three or more number network and identifier frames.

This change is in accordance with SD-32375-01, Issue 35AR. ◆

4. EQUIPMENT

The following changes apply to 4. EQUIPMENT:

- (a) J39842AA,L3—added
- ◆ (b) J38942AA,L4—added ◆
- (c) J38942AB,L2 and L3—added
- (d) J38942AC,L4—added

(e) J38942AE,L2—added

◆ (f) J38942AE,L2—removed. ◆

Under J38942AA

Add:

List 3—Apparatus and wiring per SD-32375-01, Fig 1, option ZW only, required in addition to list 1 in offices equipped with CDAs or in offices that require noise suppression.

◆ *List 4*—Wiring and apparatus per SD-32375-01, Fig 7, option ZT only, required in addition to list 1 when outpulser is associated with three or more number network and identifier frames and additional contact protection is required. ◆

Under J38942AB

Add:

List 2—Wiring and apparatus per SD-32375-01, Fig 2, option ZN only, required in addition to list 1 to provide a KP pulse delay.

List 3—Apparatus and wiring per SD-32375-01, Fig 2, option ZW only, required in addition to list 1 in offices equipped with CDAs or in offices that require noise suppression.

Under J38942AC

Add:

List 4—Apparatus and wiring per SD-32375-01, Fig 8, option ZW only, required in addition to list 1 in offices equipped with CDAs or in offices that require noise suppression.

NOTICE
This document is either
AT&T - Proprietary, or AT&T
TECHNOLOGIES, INC - Proprietary
Pursuant to Judge Greene's Order of August 5, 1983, beginning
on January 1, 1984, AT&T will cease to use "BELL" and the Bell
symbol, with the exceptions as set forth in that Order. Pursuant
thereto, any reference to "BELL" and/or the BELL symbol
in this document is hereby deleted and "expunged".

Under J38942AE

Add:

List 2—Wiring and apparatus per SD-32375-01, Fig 7, option ZT only, required in addition to list 1 when outpulser is associated with three or more number network and identifier frames and additional contact protection is required.

◆ *Remove: List 2* ◆

AT&T Bell Laboratories

Dept 55212