



- NOTES:
- A. HEADBAND WIRE SHALL BE SMOOTH AND OF ROUND CROSS-SECTION.
 - B. THIS REQUIREMENT APPLIES WHEN ENDS OF HEADBAND ARE PUSHED TO MAXIMUM DEPTH IN CRADLE.

LA-

DIMENSIONS UP TO AND INCLUDING 72 INCHES EXPRESSED IN INCHES

BL 211049 A-	
ISSUE	
ISSUE 1	8-14-47
"KINKS IN THE WIRE, ETC." WAS "WIRE SHALL NOT DEVIATE FROM THE TRUE POSITION MORE THAN 1/16 INCH AT ANY POINT THROUGHOUT ITS LENGTH."	
RBR	CHH
ISSUE 2	7-28-47
IN TITLE SEC D-404.024 WAS "SEC D-404.023"	
PAC	CHH
ISSUE 3	3-18-47
4 1/2 ± 1/8 WAS 4 3/8 ± 3/16	
"THERE SHALL BE NO NICKS OR DENTS IN WIRE" WAS NOT SPECIFIED.	
P.S.K.	CHH
ISSUE 4	11-25-47
PICTURE OF CRADLE CHANGED TO AGREE WITH LA-701897.	
J.E.D.	CHH
ISSUE 5	10-25-50
PAD WAS SHOWN ON HEADBAND	
J.E.D.	CHH
ISSUE 6	1-29-51
"KINKS OR DENTS IN, ETC." WAS "KINKS IN THE WIRE SHALL NOT EXCEED 1/16 INCH. THERE SHALL BE NO NICKS OR DENTS IN THE WIRE." MAX. .115 WAS MAX. .109.	
J.E.D.	CHH
ISSUE 7	3-26-51
"MIN. 2 1/4" DIM. WAS NOT SHOWN. HEADBAND WIRE ETC. WAS "THERE SHALL BE NO NICKS IN THE WIRE." TITLE WAS "A HEADBAND BELL SYSTEM PRACTICES 0452.024."	
AS.	R.H.F.
ISSUE 8	9-25-53
VIEW AND NOTE WERE SHOWN THIS:	
KINKS OR DENTS IN THE WIRE SHALL NOT EXCEED 1/16 INCH. HEADBAND WIRE SHALL BE FREE FROM NICKS, GROUNDS OR SCRAPE TOOL MARKS OR SETS SHALL BE HELD TO A MINIMUM. NOTES A & B & DIMS 1.875 MAX. 1.625 MIN. & 2.750 MIN. & 2.000 MIN. WERE NOT SHOWN. 4 1/2 ± 1/2 DIM WAS SHOWN ON LEFT VIEW BETWEEN E OF CRADLE AND INSIDE OF HEADBAND AT LOWER LEFT.	
SE	CHH
ISSUE 9	5-21-54
IN LEFT VIEW "HEADBAND WIRE" WAS "HEADBAND" & "PIN" WAS NOT SPEC.	
A.S.G.	CHH
ISSUE 10	11-19-54
REMOVED: 2 1/4" DIM. FROM YOKE.	
ADDED: (SEE NOTE B) TO HEADBAND DIM.	
CHANGED	
± TOLERANCE ON THE WIRES WAS	
1.875 MAX. WAS 1.625 MAX.	
FRL	
Iss. 12 7-9-62	
APPL'S	CHH
CH.	CHH
DR.	E. MIRITELLO
ENG.	W. R. LYON
BELL TELEPHONE LABORATORIES, INC. NEW YORK	
BL-211049	
LA-	

ISSUE 1 8-14-47
 "KINKS IN THE WIRE, ETC." WAS "WIRE SHALL NOT DEVIATE FROM THE TRUE POSITION MORE THAN 1/16 INCH AT ANY POINT THROUGHOUT ITS LENGTH."
 RBR CHH
 ISSUE 2 7-28-47
 IN TITLE SEC D-404.024 WAS "SEC D-404.023"
 PAC CHH
 ISSUE 3 3-18-47
 4 1/2 ± 1/8 WAS 4 3/8 ± 3/16
 "THERE SHALL BE NO NICKS OR DENTS IN WIRE" WAS NOT SPECIFIED.
 P.S.K. CHH
 ISSUE 4 11-25-47
 PICTURE OF CRADLE CHANGED TO AGREE WITH LA-701897.
 J.E.D. CHH
 ISSUE 5 10-25-50
 PAD WAS SHOWN ON HEADBAND
 J.E.D. CHH
 ISSUE 6 1-29-51
 "KINKS OR DENTS IN, ETC." WAS "KINKS IN THE WIRE SHALL NOT EXCEED 1/16 INCH. THERE SHALL BE NO NICKS OR DENTS IN THE WIRE." MAX. .115 WAS MAX. .109.
 J.E.D. CHH
 ISSUE 7 3-26-51
 "MIN. 2 1/4" DIM. WAS NOT SHOWN. HEADBAND WIRE ETC. WAS "THERE SHALL BE NO NICKS IN THE WIRE." TITLE WAS "A HEADBAND BELL SYSTEM PRACTICES 0452.024."
 AS. R.H.F.
 ISSUE 8 9-25-53
 VIEW AND NOTE WERE SHOWN THIS:

 KINKS OR DENTS IN THE WIRE SHALL NOT EXCEED 1/16 INCH. HEADBAND WIRE SHALL BE FREE FROM NICKS, GROUNDS OR SCRAPE TOOL MARKS OR SETS SHALL BE HELD TO A MINIMUM. NOTES A & B & DIMS 1.875 MAX. 1.625 MIN. & 2.750 MIN. & 2.000 MIN. WERE NOT SHOWN. 4 1/2 ± 1/2 DIM WAS SHOWN ON LEFT VIEW BETWEEN E OF CRADLE AND INSIDE OF HEADBAND AT LOWER LEFT.
 SE CHH
 ISSUE 9 5-21-54
 IN LEFT VIEW "HEADBAND WIRE" WAS "HEADBAND" & "PIN" WAS NOT SPEC.
 A.S.G. CHH
 ISSUE 10 11-19-54
 REMOVED: 2 1/4" DIM. FROM YOKE.
 ADDED: (SEE NOTE B) TO HEADBAND DIM.
 CHANGED
 ± TOLERANCE ON THE WIRES WAS
 1.875 MAX. WAS 1.625 MAX.
 FRL
 Iss. 12 7-9-62
 APPL'S CHH
 CH. CHH
 DR. E. MIRITELLO ENG. W. R. LYON
 BELL TELEPHONE LABORATORIES, INC. NEW YORK
 BL-211049
 LA-