

SECURICAM Network **Internet Camera Outdoor Enclosures**

The D-Link® Securicam Internet Camera Outdoor Enclosures provide a cost-effective solution for protecting your D-Link Internet Camera from the rigors of outdoor use. The fixed-type enclosures include heavy duty, angle-adjustable mounting brackets that can be used to secure the camera on a vertical or horizontal surface. Maximize the full potential of your D-Link Internet Cameras to secure and protect your business.

The DCS-45 includes a thermal barrier design to withstand temperature fluctuations and a flip open top for easy installation.



Supported Devices

- DCS-3220 • DCS-3220G (Wired Mode Only)
- DCS-3420 (Wired Mode Only)

Dimensions

- 14.2" (L) x 5.5" (W) x 5.5" (H)

Weight

- 3.26lb

Material

- Aluminum Housing with Steel Bracket

Color

- Light Gray Powder Coating



The DCS-50 features IP66 certification for protection against dust and heavy jets of water. This model includes a built-in power supply for easy cable management.

Supported Devices

- DCS-3220 • DCS-3220G (Wired Mode Only)
- DCS-3420 (Wired Mode Only)

Power Supply

- 110V AC Input, 12V DC, 3A Output

Dimensions

- 15.4" (L) x 5" (W) x 4.9" (H)

Weight

- 6.72lb

Material

- Aluminum Housing

Color

- White



The DCS-60 features IP44 certification for protection against splashing water. This model includes a heater and blower for camera operation in a wider range of temperature-sensitive environments. The built-in power supply simplifies the installation procedure.

Supported Devices

- DCS-3220 • DCS-3220G (Wired Mode Only)
- DCS-3420 (Wired Mode Only)

Power Supply

- 110V AC Input, 12V DC, 3A Output

Heater

- On at 64°F (±5°F), Off at 82°C (±5°F)

Blower

- On at 95°C (±5°F), Off at 77°C (±5°F)

Dimensions

- 17.7" (L) x 5.3" (W) x 5.5" (H)

Weight

- 9.47lb

Material

- Aluminum Housing

Color

- White



The DCS-70 is a dome-type enclosure and is designed for use with D-Link's motorized pan and tilt cameras. This IP66 certified enclosure protects your camera against dust and heavy jets of water. Camera installation is simplified with the built-in power supply, while the heater and blower keeps your camera in proper operating temperatures.

Supported Devices

- DCS-5300 • DCS-5300G (Wired Mode Only)
- DCS-6620 • DCS-6620G (Wired Mode Only)

Power Supply

- 110V AC Input, 12V DC, 2A Output

Heater

- On at 32°F (±9°F), Off at 50°F (±9°F)

Blower

- On at 104°F (±9°F), Off at 86°F (±9°F)

Dimensions

- 8.86" (L) x 8.58" (W) x 8.58" (H)

Weight

- 7.27lb

Material

- Aluminum Housing with Smoked Acrylic Cover

Color

- Beige