




# Dell Alienware 14 Secondary Hard Drive Replacement

Follow this guide to replace the hard drive for the Dell Alienware 14.

Written By: Terrence15



---

## INTRODUCTION


In this guide, we will show you how to remove and replace the secondary hard drive.

---

### TOOLS:

- [Pro Tech Toolkit](#) (1)
-


## Step 1 — Close the Display



**⚠ WARNING:** Before working inside your computer, read the safety information that shipped with your computer and follow the steps in [Before You Begin](#). After working inside your computer, follow the instructions in [After Working Inside Your Computer](#).

- Close the display, and turn the computer over.

## Step 2 — Remove the Screws




- Remove the screws that secure the base cover to the computer base.

### Step 3 — Slide and Lift the Base Cover



- Slide and lift the base cover off the computer base.

### Step 4 — Align the Tabs




- Align the tabs on the **NEW** base cover with the slots on the computer base and slide the base cover into place.

## Step 5 — Replace the Screws




- Replace the screws that secure the base cover to the computer base.

## Step 6 — Turn the Computer Over



- Turn the computer over and open the display.


## Step 7 — Disconnecting the Battery Cable



**⚠ WARNING:** Before working inside your computer, read the safety information that shipped with your computer and follow the steps in [Before Working Inside Your Computer](#). After working inside your computer, follow the instructions in [After Working Inside Your Computer](#).


- Disconnect the battery cable from the system-board connector.

## Step 8 — Remove the Screws




- Remove the screws that secure the battery to the computer base.

## Step 9 — Using the Battery Cable




- Using the battery cable, lift the battery and release it from the tabs on the computer base.

## Step 10 — Turn the Computer Over




- Turn the computer over and open the display as far as possible.

## Step 11 — The Power Button




- Press and hold the power button for five seconds to ground the system board.

## Step 12 — Close the Display




- Close the display and turn the computer over.

## Step 13 — Align the Tabs




- Align the tabs on the **NEW** battery with the slots on the computer base.

## Step 14 — Align the Screw Holes




- Align the screw holes on the battery with the screw holes on the computer base.

## Step 15 — Replace the Screws




- Replace the screws that secure the battery to the computer base.

## Step 16 — Connect the Battery Cable



- Connect the battery cable to the system-board connector.

## Step 17 — Remove the Screws



**⚠ WARNING:** Before working inside your computer, read the safety information that shipped with your computer and follow the steps in [Before Working Inside Your Computer](#). After working inside your computer, follow the instructions in [After Working Inside Your Computer](#).


**⚠ CAUTION:** To avoid data loss, do not remove the hard drive while the computer is On or in Sleep state.

**⚠ CAUTION:** Hard drives are extremely fragile. Exercise care when handling the hard drive.

**i NOTE:** The secondary hard-drive or solid-state drive is optional and can be installed in the optical drive bay.


- Remove the screws that secure the secondary hard-drive assembly to the computer base.

## Step 18 — Lifting the Secondary Hard-Drive




- Carefully lift the secondary hard-drive assembly and then lift the latches to release the secondary hard-drive cable from the system-board connector.

## Step 19 — Lifting the Hard Drive




- Lift the secondary hard-drive assembly off the computer base.

## Step 20 — Turn the Assembly Over




- Turn the secondary hard-drive assembly over.

## Step 21 — Remove the Screw





- Remove the screw that secures the secondary hard-drive assembly to the main bracket.

## Step 22 — Remove the Screws




- Remove the screws that secure the secondary hard-drive to the secondary hard-drive bracket.

## Step 23 — Slide and Lift the Hard-Drive




- Slide and lift the secondary hard-drive off the secondary hard-drive bracket.

## Step 24 — Disconnect the Interposer




- Disconnect the interposer from the secondary hard-drive connector.

## Step 25 — Connect the Interposer




- Connect the interposer to the secondary hard-drive connector.

## Step 26 — Placing the Secondary Hard-Drive




- Place the **NEW** secondary hard-drive in the secondary hard-drive bracket.

## Step 27 — Align the Screw Holes




- Align the screw holes on the secondary hard-drive with the screw holes on the secondary hard-drive bracket.

## Step 28 — Replace the Screws




- Replace the screws that secure the secondary hard-drive to the secondary hard-drive bracket.

## Step 29 — Align the Screw Hole




- Align the screw hole on the secondary hard-drive assembly with the screw hole on the main bracket.

### Step 30 — Replace the Screw




- Replace the screw that secures the secondary hard-drive assembly to the main bracket.

### Step 31 — Turn the Hard-Drive Assembly Over




- Turn the secondary hard-drive assembly over.

## Step 32 — Slide the Hard-Drive Cable



- Slide the secondary hard-drive cable into the system-board connector and press down on the connector latches to secure the cable.

## Step 33 — Align the Screw Holes



- Align the screw holes on the secondary hard-drive assembly with the screw holes on the computer base.

## Step 34 — Replace the Screws



- Replace the screws that secure the secondary hard-drive assembly to the computer base.

To reassemble your device, follow these instructions in reverse order.