




Lenovo ThinkPad X1 Carbon 6th Gen Motherboard Replacement

This guide details how to replace the motherboard in a Lenovo ThinkPad X1 Carbon 6th Gen.

Written By: Michael Megna



INTRODUCTION

In this guide, you will learn how to replace the motherboard in a Lenovo ThinkPad X1 Carbon 6th Gen. Be sure to power off your device and disconnect it from any power source before beginning.

TOOLS:

- [Phillips #0 Screwdriver](#) (1)
 - [iFixit Opening Tools](#) (1)
 - [iFixit Opening Picks set of 6](#) (1)
 - [Nylon Tipped Tweezers](#) (1)
-

Step 1 — Back Cover




- Use a Phillips #0 screwdriver to loosen the five screws that secure the back cover to the laptop.
- ⓘ The screws do not completely come off from the back cover. Loosen until the screws are completely loose.

Step 2



- Use a Jimmy to lift the cover directly up off of the locating pins.
- ⓘ Though a metal opening tool is shown in the image, we recommend using plastic opening tools to minimize any cosmetic damage.
- Once the case is lifted enough using the tool, grab the cover and take it the rest of the way off.
- ⓘ If you encounter resistance when lifting the cover, revisit the screws to see if any of them are still threaded on to the device.

Step 3 — Fan





- Use a Phillips #0 screwdriver to loosen the four screws that secure the fan to the motherboard.
- ⓘ The screws do not completely come off from the fan mount. Loosen until the screws are completely loose.

Step 4



- Use nylon tipped tweezers, or your fingers, to gently pull the fan's power cable towards the SSD, disconnecting it from the pins.
- ⓘ Be sure to pull on all of the cables at the same time.

Step 5



- Use a plastic opening pick to lift the fan mount.
- Use your fingers to gently pull the fan diagonally away from where it is connected.

Step 6




- Turn the fan over to expose the interior.
- If necessary, clean out the fan or wipe away and replace the thermal paste.

Step 7 — Motherboard




- Remove each of the 7 main ribbon cables that connect the motherboard to the rest of the laptop.
 - Detach the last ribbon cable in the same way as before.
- ⚠ These connectors and cables are all very fragile. Handle with care.
- For the red and orange cables, use a spudger to lift the black plastic bar.
- ⓘ The bar should be lifted to the point where it can move easily.

Step 8





- Place a spudger under the cables to disconnect them from the WAN card.
- ⓘ Tweezers or a hook may also be used for this step.

Step 9




- Use a Phillips #00 screwdriver to remove the two 3mm screws that secure the IO bracket.

Step 10




- i** The antenna brackets act as a securing mount for the motherboard to the device.
- Remove the two 3mm antenna bracket screws using a Phillips #00 screwdriver.

Step 11




- Lift from the location of the screw towards you. Then pull towards the screw side to remove the bracket.

Step 12




- i The housing for the SD card slot is directly attached to the device.
- Remove and unscrew the two 5mm screws with a Phillips #0 screwdriver..

Step 13





- Using an iFixit SIM card screw head tip, apply pressure to the hole to disconnect the SD card slot from the device.

Step 14



- Use a Phillips #00 screwdriver to remove each of the four remaining 3mm screws securing the motherboard to the device.

Step 15



- Lift from the top of the motherboard towards you.
- Pull away from the IO port side to remove the motherboard.

To reassemble your device, follow these instructions in reverse order.