



# MacBook Air 13" Mid 2012 Solid-State Drive Replacement

Replace the solid state drive in your MacBook Air 13" Mid 2012.

Written By: Andrew Optimus Goldheart



## INTRODUCTION

Use this guide to upgrade or replace the solid-state drive in a MacBook Air 13" Mid 2012. This MacBook Air uses a [proprietary storage drive connector](#), and is therefore **not compatible** with common M.2 and mSATA drives without the use of an adapter.

**Before you perform this repair**, if at all possible, [back up your existing SSD](#). Then, either familiarize yourself with [internet recovery](#) or [create a bootable external drive](#) so you'll be ready to install macOS onto your new drive and migrate your data to the new SSD.

Finally, we strongly recommend installing macOS 10.13 High Sierra (or a later macOS) before replacing the original SSD from your MacBook Air. Most new SSDs require updated storage drivers not found in versions of macOS prior to High Sierra.

### TOOLS:

- [P5 Pentalobe Screwdriver Retina MacBook Pro and Air](#) (1)
- [T5 Torx Screwdriver](#) (1)

### PARTS:

- [Macbook Air 11" and 13" \(Mid 2012\) SSD](#) (1)
- [OWC Aura Pro 6G SSD for Macbook Air 11" and 13" \(Mid 2012\)](#) (1)

## Step 1 — Lower Case




- ⓘ Before proceeding, power down your MacBook. Close the display and lay it on a soft surface, top-side down.
- Use a [P5 Pentalobe](#) driver to remove ten screws securing the lower case, of the following lengths:
  - Two 9 mm screws
  - Eight 2.6 mm screws

## Step 2




- Wedge your fingers between the display and the lower case and pull upward to pop the lower case off the Air.
- Remove the lower case and set it aside.

### Step 3 — Battery Connector



- i** As a precaution against accidental discharge or shock, disconnect the battery connector from the logic board.
- Grab the clear plastic pull tab attached to the battery connector and pull it toward the front edge of the Air to disconnect the battery from the logic board.
- !** Be sure to pull the connector horizontally toward the battery, and not straight up from the Air, or you may damage the socket on the logic board.

## Step 4 — Solid-State Drive



- Remove the single 2.9 mm T5 Torx screw securing the SSD to the logic board.

## Step 5



⚠ To avoid damaging its socket, do not lift the end of the SSD excessively.

- Slightly lift up the end of the SSD and pull it straight out of its socket on the logic board.
- ☑ When reinstalling the SSD, be sure it is properly seated before reinstalling its retaining screw.

To reassemble your device, follow these instructions in reverse order.