




Samsung Galaxy S10+ Loudspeaker Replacement

Remove the loudspeaker, which is molded into the lower midframe, for the Samsung Galaxy S10+ (S10 plus).

Written By: Arthur Shi



This document was generated on 2020-03-05 06:21:17 AM (MST).

INTRODUCTION

Follow this guide to remove the loudspeaker for the Samsung Galaxy S10+. For this model, the loudspeaker is built into the lower midframe.

TOOLS:

- [iOpener](#) (1)
- [iFixit Opening Tools](#) (1)
- [Suction Handle](#) (1)
- [iFixit Opening Picks set of 6](#) (1)
- [Tweezers](#) (1)
- [Phillips #00 Screwdriver](#) (1)
- [Spudger](#) (1)

PARTS:

- [Galaxy S10 Plus \(Global\) Speaker](#) (1)

Step 1 — Back Cover



- Unplug and power off your phone before you begin.
- [Heat an iOpener](#) and apply it to the **back cover's right edge** for two minutes.
 - ⓘ A hair dryer, heat gun, or hot plate may also be used, but be careful not to overheat the phone—the display and internal battery are both susceptible to heat damage.
- As you wait, take a look at the image of the removed back cover and take note of where the adhesive is located.

Step 2



- Heat an iOpener and apply it to the same edge of the phone for two minutes.
 - Apply a suction cup to the back of the phone, as close to the center of the right edge as possible ([where the adhesive is narrowest](#)).
 - Pull on the suction cup with strong, steady force to create a gap between the back cover and the frame.
 - Insert the point of an opening pick into the gap.
- i** Due to tight tolerances, this may take multiple attempts.
- If you are having trouble creating a gap, your best bet is to apply more heat to the edge and try the previous step again.
 - You can try applying a few drops of high concentration (over 90%) isopropyl alcohol into the seam to help loosen the adhesive.
- ⚠** Do not apply excessive force with the pick, or you will risk cracking the back cover glass.

Step 3



- Rest the heated right edge of the phone on something that is about 0.5 inches (13 mm) thick. This angles the phone for the opening tool.
- Brace the left edge of the phone with your fingers so that the phone won't slide. Pull on the suction cup with firm pressure.
- Press the edge of an opening tool into the seam between the back cover and the frame.
- Slide the opening tool back and forth along the seam a few times.

Step 4



- Slide the opening pick along the edge of the phone, slicing through the adhesive.
- ⚠ Do not attempt to slice the adhesive holding the corners down before applying heat. If you do, you may crack the back cover.
- Leave a pick in the seam to prevent the adhesive from re-sealing.

Step 5



- Apply a heated iOpener to the bottom edge of the phone for two minutes.
- Insert an opening pick into the right edge near the bottom right corner.
- Carefully slide the pick around the corner. Continue cutting along the bottom edge and around the bottom left corner.
 - ⓘ If the cutting feels difficult, re-apply heat to the edge before continuing.
- Leave an opening pick in the seam to prevent the adhesive from re-sealing.

Step 6




- Continue heating and slicing around the remaining edges of the phone.
 - ⓘ When cutting around corners, be sure that the corner is thoroughly heated.

Step 7





- Once you have sliced around the phone, twist an opening pick in one of the edges to help separate the back cover from the frame.
- Lift the back cover slowly. Use opening picks to slice any remaining adhesive.
- Remove the back cover.
- ☑ During reassembly, this is a good point to power on your phone and test all functions before you seal the back cover in place. Be sure to power your phone back down completely before you continue working.
- ☑ [Follow this guide](#) to reinstall the back cover, transfer and install the camera bezel, and replace the adhesive.

Step 8 — Samsung Galaxy S10+ Top Midframe Removal



- Remove the nine 4 mm Phillips screws securing the top midframe to the phone.


Step 9



- ⓘ The midframe is still held in place by a few plastic clips around the edge.
 - Insert the point of a spudger into the notch on the right edge of the midframe, near the Bixby button.
 - Pry up to loosen the midframe from the phone.

This document was generated on 2020-03-05 06:21:17 AM (MST).

Step 10



- Insert the point of a spudger into the notch on the left edge of the phone, located near the power button.
- Pry up to loosen the midframe from the phone.

Step 11



- Lift the midframe from the top corners and remove it from the phone.
- ★ To reinstall the top midframe:
 - [Align the midframe's top edge to the phone](#) and lay the frame down on the phone.

- [Use fingers to apply pressure along the midframe perimeter](#) to snap the midframe clips back into


place. The edges should sit flush against the phone edge.

Step 12 — Loudspeaker




- Remove the seven 4 mm Phillips screws securing the lower midframe to the phone.

Step 13



- i** The midframe is still held in place by a few plastic clips around the edge.
- Insert the point of a spudger in the notch near the bottom right corner of the lower midframe. It is marked by a small triangle.
 - Pry up to release the midframe from the phone.

Step 14



- Grasp the loosened end of the midframe with your fingers and lift upwards slowly.
 - Wiggle the midframe slightly to help release the remaining edge clips.
 - Remove the lower midframe. The loudspeaker is built into the lower midframe.
- To reinstall the lower midframe, align the midframe's bottom edge to to the phone edge, and press it into place.

To reassemble your device, follow these instructions in reverse order.

Repair didn't go as planned? Check out our [Answers community](#) for troubleshooting help.